



NOMINAL DIAMETAR DN	MAX. WORK PRESSURE For NP 6 (bar)	
	< 120 °C	120 °C – 180 °C
15 – 250	6	5

NOMINAL DIAMETAR DN	MAX. WORK PRESSURE For NP 16 (bar)	
	< 120 °C	120 °C – 180 °C
15 – 175	16	10
200 – 250	10	6

VERSION B – body: cast iron; internal parts: stainless steel

VERSION C – body: cast iron; internal parts: brass or bronze

VERSION D – body: bronze; internal parts: brass or bronze

VERSION H – body: GGG 40; internal parts: brass or bronze

VERSION K – body: GGG 40; internal parts: stainless steel

NP 6

NP 16

NOMINAL DIAMETAR DN	d ₁	b VERSION B, C, H i K		k	d ₂	n.	l	h ₂
		D	D					
15	80	12	10	55	11	4	130	206
20	90	14	12	65			150	
25	100			16	14	75	160	230
32	120	18	16			90	180	
40	130			20	18	100	200	268
50	140	22	20			110	230	
65	160			24	22	130	290	304
80	190	26	24			150	310	
100	210			28	26	170	350	396
125	240	30	28			200	400	
150	265			32	30	225	480	514
175	295	34	32			255	550	
200	320			36	34	280	600	601
250	375	38	36			335	730	

NOMINAL DIAMETAR DN	d ₁	b VERSION B, C, H i K		k	d ₂	n.	l	h ₂
		D	D					
15	95	14	12	65	14	4	130	206
20	105	16	14	75			150	
25	115			18	16	85	160	230
32	140	20	18			100	180	
40	150			22	20	110	200	268
50	165	24	22			125	230	
65	185			26	24	145	290	304
80	200	28	26			160	310	
100	220			30	28	180	350	396
125	250	32	30			210	400	
150	285			34	32	240	480	514
175	315	36	34			270	550	
200	340			38	36	295	600	601
250	405	40	38			355	730	